Fogging Machine

No.	Technical Specification	Fill Your Specifications
1	Portable Thermal fog applicator, pulse-jet engine, simple manual operated pump, Dimensions 135 x 30 x 30 Cm, Power ignition electronic ignition coil, Weight (empty) 8-9 Kg	
2	4 dry batteries 1,5 V, Chemical tank, stainless or heavy polyethylene, capacity 6-10 liter, Fuel consumption approx. 2 L/h with, High performance fogging tube (for water-based fogging mixtures), output dosage nozzle 0.7 - 1.1 (10-20L/h), Droplet Size less than 20 Microns, with mounting frame and strap, Standard maintenance kit, Standard accessories (fuel funnel with strainer (mesh width 0.1 mm)	
3	chemical funnel with strainer (mesh width 0.1 mm) tool kit cleaning equipment set of spares (gaskets, O-rings, diaphragms)	
4	carrying strap ear protection (2 sets)	
5	instruction manual (English and Arabic language) including spare parts list) IPARC -WHO - certificate of Compliance	

Spare Parts fogging Machine

No.	Technical Specification	Fill Your Specifications
1	High performance fogging tube -Special fog tube for water (for water-based fogging mixtures), output dosage range 0.7 - 1.1 (10-20L/h), Droplet Size less than	
'	20 Microns	

<u>Ultra Low Volume Pump</u>

No.	Technical Specification	Fill Your Specifications
1	Vehicle -mounted ULV aerosol generators, For -cycle internal combustion engine, Engine 18 HP, Battery 12 V, Blower Roots (350 CFM), Dimensions 90x80x100 Cm, Weight (Empty) 215-230 KG, Fuel Tank Capacity 30-40 liters, air compressor, Metal mounting frame for engine, insecticides metering system, Droplet Size 90% less than 20 Microns, Flexible movement nozzle, Solvent-flushing system and remote controls, directional spiral volutes or with movable air vanes in a stationary volute, insecticide tank 60 liter, Calibration manual (English and Arabic) with CD video, IPARC - WHO certificate of Compliance, Standard accessories (tool kit, chemical funnel with strainer (mesh width 0.1 mm), ear protection, 2 sets, PPE(Overall, boot), instruction manual (English and Arabic) with spare parts list, heavy duty sealed dry battery, 12 V / 36 Ah, additional dosage nozzle)	

Spare Parts of Ultra Low Volume Pump

No.	Technical Specification	Fill Your Specifications
1	Standard Set of Sprat (Nozzles) , consumable items	